

CLAIMS

What is claimed is:

1. A digital image capturing module assembly, which comprises:
 - a lens holder, which has one side defined as a focusing plane, and which is formed with a plurality of aligning posts on the periphery of the focusing plane;
 - a washer, which is mounted on the periphery of the focusing plane of the lens holder; and
 - a photosensitive printed circuit board, which is formed with a plurality of aligning holes corresponding to the aligning posts on the lens holder, and which is mounted on the washer on the lens holder by fitting the aligning holes thereof to the aligning posts on the lens holder;wherein
 - the respective tips of the aligning posts on the lens holder are each melted into a bolting structure to secure the photosensitive printed circuit board firmly in position on the lens holder;
 - and wherein
 - the firmly-secured photosensitive printed circuit board forcefully presses against the washer to thereby allow the washer to provide a sealed light-impenetrable effect at the junction between the photosensitive printed circuit board and the lens holder.
2. The digital image capturing module assembly of claim 1, wherein the photosensitive printed circuit board is a CCD-based photosensitive printed circuit board.

3. The digital image capturing module assembly of claim 1, wherein the aligning posts on the lens holder are made of plastics.
4. The digital image capturing module assembly of claim 1, wherein the washer is made of rubber.
5. The digital image capturing module assembly of claim 1, wherein the washer is formed with a plurality of aligning holes which are fitted to the aligning posts on the lens holder to help the washer secured in position on the lens holder.
6. A method for fabricating a digital image capturing module, comprising:
 - preparing a lens holder which has one side defined as a focusing plane, and which is formed with a plurality of aligning posts on the periphery of the focusing plane;
 - preparing a photosensitive printed circuit board which is formed with a plurality of aligning holes corresponding to the aligning posts on the lens holder;
 - mounting a washer on the periphery of the focusing plane of the lens holder;
 - mounting the photosensitive printed circuit board in position on the washer on the lens holder by fitting the aligning holes in the photosensitive printed circuit board to the aligning posts on the lens holder;
 - melting the respective tips of the aligning posts on the lens holder so as to transform the respective tips of the aligning posts into a bolting structure to secure the photosensitive printed circuit board in position on the lens holder as well as to allow the photosensitive printed circuit board to forcefully presses against the washer to thereby allow the washer to provide a sealed light-impenetrable effect at the junction between the photosensitive printed circuit board and the lens holder.

7. The method of claim 6, wherein the photosensitive printed circuit board is a CCD-based photosensitive printed circuit board.
8. The method of claim 6, wherein the aligning posts on the lens holder are made of plastics.
9. The method of claim 6, wherein the washer is made of rubber.
10. The method of claim 6, wherein the washer is formed with a plurality of aligning holes which are fitted to the aligning posts on the lens holder to help the washer secured in position on the lens holder.

* * * * *